16OZ SS 211x604
133213

QuestVapco

Slick
Lubricant

Anchor™ 133213 600005574 10/5/11

Slick

Lubricant
Lubricante

Contains PTFE and Moly
Loosens Nuts & Bolts
Lubricates
Prevents Rust & Corrosion
Displaces Moisture

DANGER/PELIGRO:
FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED
CONTENTS UNDER PRESSURE
KEEP OUT OF REACH OF CHILDREN
SEE ADDITIONAL CAUTIONS ON BACK PANEL
INFLAMABLE. DAÑINO O FATAL SI ES INGERIDO
CONTENIDO BAJO PRESIÓN
NO SE DEJE AL ALCANCE DE LOS NIÑOS
VEA PRECAUCIONES ADICIONAL EN EL PANEL TRASERO

NET WT. 12 OZ. (340 g)

QuestVapco Corporation
Houston, TX • St. Louis, MO

Scientifically formulated penetrating oil and rust dissolver containing micron size particles of PTFE and Moly. This super penetrant carries the PTFE and molybdenum disulfide particles into the threads, crevices, etc. These particles act as millions of tiny ball bearings to prevent seizing and galling while the parts are being removed. This product is designed to be used on all dismantling jobs throughout the plant, shop or wherever parts are frozen or hard to operate. Quickly loosens corroded nuts, studs, bolts, flanges and pipe joints.

DIRECTIONS FOR USE: Shake well. Remove protective cap and point spray opening in desired direction. Holding container 6-12 inches from surface to be treated, spray product liberally, saturating joints. Allow to set 5-10 minutes and break out. For extremely difficult jobs, saturate joints and allow to set 5-10 minutes, then tap lightly with a hammer and break out.

MODO DE EMPLEO: Agite bien antes de usar. Remueva la tapa protectora y apunte en la dirección deseada. Sostenga el contenedor de 6 a 12 pulgadas de la superficie que se va a tratar, rocíe el producto con libertad hasta saturar las juntas. Espere de 5 a 10 minutos para desatorar. Para trabajos extremadamente difíciles, sature las juntas y permita que actúe de 5 a 10 minutos, después golpee ligeramente con un martillo para desatorar.

DANGER: FLAMMABLE. Contains Petroleum Distillates. Do not use near fire or open flame. Contents under pressure. Do not puncture. Do not store above 120°F. Do not throw container into fire or incinerator. Avoid frequent or prolonged contact with skin. Use only in well ventilated area. If swallowed, do not induce vomiting. Contact physician immediately.

PELIGRO: INFLAMABLE: Contiene destilados de petróleo. No use cerca del fuego o llamas. Contenido bajo presión. No perfore. No almacene por encima de 120°F. No tire el contenedor al fuego o incinerador. Evite el contacto frecuente o prolongado con la piel. Use solo en áreas bien ventiladas. Si es ingerido, no induzca vomito. Contacte a un médico inmediatamente.

INGREDIENTS (CAS#): Petroleum Distillate (64741-44-2), Isoparaffinic Hydrocarbon (64742-47-8), Propane/n-Butane (68476-86-8), Petroleum Distillate (64742-54-7), Ethyl Acetate (141-78-6).

HEALTH	1
FLAMMABILITY	2
REACTIVITY	0
PERSONAL	A



8 31788 00086 5

ITEM 574000001 Made in USA

574_QUEST_SLICK.indd 1 CYAN MAG YEL BLACK 10/7/11 1:14 PM